

Part #97-09000**Model SR9**

Performance	12VDC / 24VDC
Single line rated pull	9000lb(4300kg)
Motor	5.5hp/4.0kw, Series Wound
Control	Remote switch, 12ft(3.7m)lead
Gear train	3 Stage Planetary
Gear reduction ratio	235:1
Clutch	Sliding Ring Gear
Braking Action	Automatic In-The-Drum
Drum size	Drum size Diameter 2.5"(63.5mm) Length 8.8"(224mm)
Cable	94ft of 21/64" diameter(28m of 8.3mm diameter)
Fairlead	4-Way Roller Fairlead
Remote Control	Included
Battery	Recommended: 650CCA minimum for winching
Battery Leads	2 gauge, 72"(1.83m)
Finish	Satin Black
Weight	N.W.: 37kg G.W.: 39kg
Overall dimensions	(LxWxH) 21.3"x6.3"x8.6"(562x160x218mm)
Mounting Bolt Pattern	10.00±0.015"x4.50±0.010"(254x114.3mm)

Speed, Amperes, Volts (First Layer)

Line Pull (lbs./ kg)	Line Speed FPM(m/min)	Motor (Amps)
0	24.6ft (7.8m)	60
2000 (907)	14.4ft (4.4m)	90
4000 (1818)	10ft (3m)	130
6000 (2727)	8.5ft (2.6m)	190
8000 (3636)	6.9ft (2.1m)	280
9000 (4090)	5.2ft (1.6m)	340

Line Pull And Rope Capacity In Layer

Layer	Rated Line Pull (lbs./kgs)	Total Rope On Drum (ft/m)
1	9000 (4090)	16.2 (5)
2	7300 (3318)	39 (12)
3	6150 (2795)	68.2 (21)
4	5400 (2454)	92 (28)