

**Part #97-10000****Model SR10**

Performance	12VDC
Single line rated pull	10000lb(4536kg)
Motor	5.6hp/4.2kw, Series Wound
Control	Remote switch, 12ft(3.7m)lead
Gear train	3 Stage Planetary
Gear reduction ratio	265.2:1
Clutch	Sliding Ring Gear
Braking Action	Automatic In-The-Drum
Drum size	Drum size Diameter2.5"(63.5mm) Length 8.8"(224mm)
Cable	85ft of 3/8" diameter(28m of 9.2mm diameter)
Fairlead	4-Way Roller Fairlead
Remote Control	Included
Battery	Recommended:650CCA minimum for winching
Battery Leads	2 gauge,72"(1.83m)
Weight	N.W.:38kg G.W.:40kg
Overall dimensions	(LxWxH)21.3"x6.3"x8.6"(552x160x218mm)
Mounting Bolt Pattern	10.00±0.015"x4.50±0.010"(254x114.3mm)

**Pull, Speed, Amperes, Volts (First Layer)**

Line Pull (lbs./ kg)	Line Speed FPM(m/min)	Motor (Amps)
0	22.0ft (6.8m)	80
4000 (1818)	11.5ft (3.5m)	170
6000 (2727)	9.2ft (2.8m)	220
8000 (3636)	6.9ft (2.1m)	280
10000 (4545)	4.9ft (1.5m)	370

**Line Pull And Rope Capacity In Layer**

Layer	Rated Line Pull (lbs./kgs)	Total Rope On Drum (ft/m )
1	10000 (4545)	19.6 (6.0)
2	8000 (3636)	42.6 (13.0)
3	6670 (3030)	72.0 (22.0)
4	5720 (2600)	85.0 (26.0)