

Part #97-10000S**Model SR10S**

Performance	12VDC
Single line rated pull	10000lb(4536kg)
Motor	5.6hp/4.2kw, Series Wound
Control	Remote switch, 12ft(3.7m)lead
Gear train	3 Stage Planetary
Gear reduction ratio	265.2:1
Clutch	Sliding Ring Gear
Braking Action	Automatic In-The-Drum
Drum size	Drum size Diameter2.5"(63.5mm) Length 8.8"(224mm)
Synthetic Rope	85ft of 3/8" diameter
Fairlead	Hawse
Remote Control	Included
Battery	Recommended:650CCA minimum for winching
Battery Leads	2 gauge,72"(1.83m)
Weight	N.W.:27kg G.W.:29kg
Overall dimensions	(LxWxH)21.3"x6.3"x8.6"(552x160x218mm)
Mounting Bolt Pattern	10.00±0.015"x4.50±0.010"(254x114.3mm)

Pull, Speed, Amperes, Volts (First Layer)

Line Pull (lbs./ kg)	Line Speed FPM(m/min)	Motor (Amps)
0	22.0ft (6.8m)	80
4000 (1818)	11.5ft (3.5m)	170
6000 (2727)	9.2ft (2.8m)	220
8000 (3636)	6.9ft (2.1m)	280
10000 (4545)	4.9ft (1.5m)	370

Line Pull And Rope Capacity In Layer

Layer	Rated Line Pull (lbs./kgs)	Total Rope On Drum (ft/m)
1	10000 (4545)	19.6 (6.0)
2	8000 (3636)	42.6 (13.0)
3	6670 (3030)	72.0 (22.0)
4	5720 (2600)	85.0 (26.0)